

Claims

We claim:

1. A computer-implemented method for programmatically generating a graphical program, the method comprising:
- 5 displaying a graphical user interface (GUI) on a display;
- receiving user input to the GUI specifying desired functionality of the graphical program;
- programmatically generating the graphical program in response to the user input
- 10 specifying the functionality of the graphical program, wherein the graphical program implements the specified functionality.
2. The method of claim 1,
- wherein the GUI comprises information useable in guiding a user in creation of a
- 15 program.
3. The method of claim 1,
- wherein the GUI comprises one or more GUI input panels;
- wherein the user input to the GUI comprises user input to each of the one or more
- 20 GUI input panels.
4. The method of claim 3,
- wherein said displaying the GUI and said receiving user input to the GUI comprise:
- 25 displaying a first GUI input panel on the display, wherein the first GUI input panel includes one or more first fields adapted to receive user input specifying first functionality of the graphical program;
- receiving first user input specifying first functionality of the graphical program;

displaying a second GUI input panel on the display, wherein the second GUI input panel includes one or more second fields adapted to receive user input specifying second functionality of the graphical program;

receiving second user input specifying second functionality of the graphical program.

5 5. The method of claim 4,
 wherein the second GUI input panel is one of a plurality of possible second GUI input panels, wherein the second GUI input panel is displayed based on the first user
10 input.

6. The method of claim 1,
 wherein said programmatically generating the graphical program comprises programmatically generating a portion of a graphical program.

15 7. The method of claim 1,
 wherein said programmatically generating the graphical program creates the graphical program without any user input specifying the new graphical program during said creating.

20 8. The method of claim 1,
 wherein the programmatically generated graphical program comprises a plurality of interconnected nodes that visually indicate functionality of the graphical program.

25 9. The method of claim 1,
 wherein the graphical program comprises a block diagram portion comprising a plurality of interconnected nodes and a user interface portion;
 wherein said programmatically generating the graphical program includes generating the block diagram portion and the user interface portion.

10. The method of claim 1, wherein said programmatically generating the graphical program comprises:

creating a plurality of graphical program objects in the graphical program; and
5 interconnecting the plurality of graphical program objects in the graphical program;

wherein the interconnected plurality of graphical program objects comprise at least a portion of the graphical program.

10 11. The method of claim 1, wherein said programmatically generating the graphical program comprises:

creating one or more user interface objects in the graphical program, wherein the one or more user interface objects perform one or more of providing input to or displaying output from the graphical program.

15 12. The method of claim 1,
wherein the user input received specifies an instrumentation function;
wherein the programmatically generated graphical program implements the specified instrumentation function.

20 13. The method of claim 12,
wherein the instrumentation function comprises one or more of:
a test and measurement function; or
an industrial automation function.

25 14. The method of claim 1,
wherein said programmatically generating the graphical program comprises calling an application programming interface (API) enabling the programmatic generation of a graphical program.

15. The method of claim 1,
wherein said programmatically generating the graphical program comprises
programmatically requesting a server program to generate the graphical program.

5

16. A computer-implemented method for programmatically generating a
graphical program, the method comprising:

10 displaying a plurality of GUI input panels on a display, wherein the GUI input
panels comprise information useable in guiding a user in creation of a program;

receiving user input to the plurality of GUI input panels, wherein the user input
specifies desired functionality of the graphical program;

15 programmatically generating the graphical program in response to the user input
specifying the functionality of the graphical program, wherein the graphical program
implements the specified functionality.

17. A computer-implemented method for programmatically generating a
20 graphical program, the method comprising:

displaying a graphical user interface (GUI) on a display;

receiving user input to the GUI specifying desired functionality of the graphical
program;

executing a graphical program generation (GPG) program;

25 the GPG program receiving the user input, wherein the user input specifies the
desired functionality of the new graphical program;

the GPG program programmatically generating the graphical program in response
to the user input specifying the functionality of the graphical program, wherein the
graphical program implements the specified functionality.

22. The method of claim 21,
wherein the one or more input panels comprise a graphical user interface (GUI)
useable in guiding a user in specifying program functionality;
5 wherein the received user input specifies desired functionality of the graphical
program;
wherein the programmatically generated graphical source code implements the
specified desired functionality.

10

23. A computer-implemented method for programmatically generating a
graphical program, the method comprising:
displaying a node in the graphical program in response to user input;
displaying a graphical user interface (GUI) for configuring functionality for the
15 node in response to user input;
receiving user input via the GUI indicating desired functionality for the node;
programmatically including graphical source code associated with the node in the
graphical program, wherein the programmatically included graphical source code
implements the desired functionality.

20

24. The method of claim 23,
wherein said programmatically including graphical source code associated with
the node in the graphical program comprises programmatically including the graphical
source code as a sub-program of the graphical program, wherein the node represents the
25 sub-program.

25. The method of claim 23,

wherein said programmatically including graphical source code associated with the node in the graphical program comprises replacing the node in the graphical program with the programmatically included graphical source code.

5

26. A method for configuring a node in a graphical program, the method comprising:

displaying the node in the graphical program;

displaying a graphical user interface (GUI) associated with the node, wherein the
10 GUI comprises information useable in guiding a user in specifying desired functionality for the node;

receiving user input to the GUI specifying desired functionality for the node;

programmatically generating graphical source code associated with the node to
implement the specified functionality.

15

27. The method of claim 26,

wherein said programmatically generating graphical source code associated with the node comprises programmatically generating the graphical source code as a sub-program of the graphical program, wherein the node represents the sub-program.

20

28. The method of claim 26,

wherein said programmatically generating graphical source code associated with the node comprises replacing the node in the graphical program with the programmatically generated graphical source code.

25

29. The method of claim 26,

wherein no graphical source code is associated with the node until after said programmatically generating graphical source code associated with the node.

0986455-062001

30. The method of claim 26,
wherein default graphical source code is associated with the node;
wherein said programmatically generating graphical source code associated with
the node comprises replacing the default graphical source code with the programmatically
5 generated graphical source code.

31. The method of claim 26,
wherein no functionality is defined for the node until after said programmatically
generating graphical source code associated with the node.

10

32. The method of claim 26,
wherein no program instructions to be executed during execution of the graphical
program are associated with the node until after said programmatically generating
graphical source code associated with the node.

15

33. The method of claim 26, further comprising:
receiving user input requesting to change functionality of the node, after said
programmatically generating the graphical source code;
re-displaying the GUI in response to the user input requesting to change
20 functionality of the node;
receiving user input to the GUI specifying new functionality for the node;
programmatically replacing the previously generated graphical source code with
new graphical source code to implement the new functionality for the node.

25

34. A memory medium for programmatically generating a graphical program,
the memory medium comprising program instructions executable to:
display a graphical user interface (GUI) on a display;

receive user input to the GUI specifying desired functionality of the graphical program;

programmatically generate the graphical program in response to the user input specifying the functionality of the graphical program, wherein the graphical program
5 implements the specified functionality.

35. The memory medium of claim 34,
wherein the GUI comprises information useable in guiding a user in creation of a
program.

10

36. The memory medium of claim 34,
wherein the GUI comprises one or more GUI input panels;
wherein the user input to the GUI comprises user input to each of the one or more
GUI input panels.

15

37. The memory medium of claim 36, wherein the program instructions
executable to display the GUI and the program instructions executable to receive user
input to the GUI comprise program instructions executable to:

display a first GUI input panel on the display, wherein the first GUI input panel
20 includes one or more first fields adapted to receive user input specifying first
functionality of the graphical program;

receive first user input specifying first functionality of the graphical program;

display a second GUI input panel on the display, wherein the second GUI input
panel includes one or more second fields adapted to receive user input specifying second
25 functionality of the graphical program;

receive second user input specifying second functionality of the graphical
program.

38. The memory medium of claim 37,

wherein the second GUI input panel is one of a plurality of possible second GUI input panels, wherein the second GUI input panel is displayed based on the first user input.

5 39. The memory medium of claim 34,
 wherein said programmatically generating the graphical program comprises
programmatically generating a portion of a graphical program.

 40. The memory medium of claim 34,
10 wherein said programmatically generating the graphical program creates the
graphical program without any user input specifying the new graphical program during
said creating.

 41. The memory medium of claim 34,
15 wherein the programmatically generated graphical program comprises a plurality
of interconnected nodes that visually indicate functionality of the graphical program.

 42. The memory medium of claim 34,
 wherein the graphical program comprises a block diagram portion comprising a
20 plurality of interconnected nodes and a user interface portion;
 wherein said programmatically generating the graphical program includes
generating the block diagram portion and the user interface portion.

 43. The memory medium of claim 34, wherein the program instructions
25 executable to programmatically generate the graphical program comprise program
instructions executable to:

 create a plurality of graphical program objects in the graphical program; and
 interconnect the plurality of graphical program objects in the graphical program;

wherein the interconnected plurality of graphical program objects comprise at least a portion of the graphical program.

44. The memory medium of claim 34,
5 wherein the user input received specifies an instrumentation function;
wherein the programmatically generated graphical program implements the
specified instrumentation function.

45. The memory medium of claim 44,
10 wherein the instrumentation function comprises one or more of:
a test and measurement function; or
an industrial automation function.

46. A memory medium for configuring a node in a graphical program, the memory medium comprising program instructions executable to:

- display the node in the graphical program;
- display a graphical user interface (GUI) associated with the node, wherein the GUI comprises information useable in guiding a user in specifying desired functionality for the node;
- receive user input to the GUI specifying desired functionality for the node;
- programmatically generate graphical source code associated with the node to implement the specified functionality.

25 47. The memory medium of claim 46,
 wherein said programmatically generating graphical source code associated with
the node comprises programmatically generating the graphical source code as a sub-
program of the graphical program, wherein the node represents the sub-program.

